


data SHEET



Automation Platform

The EIAP5G Automation Platform is the ideal platform for your automation software solution. With its 1.2GHz CPU and 512MB of RAM the Automation Platform provides more than ample horsepower for the most demanding software applications.

Product Features

- 1.2GHz ARMv5TE CPU Marvell 88F6281
- 512MB DDR2 RAM
- Bootable microSD card slot or embedded eMMC Flash device (8GB)
- Linux Version 3.4.x.
- 802.11b/g/n Wi-Fi
- EnOcean (optional)
- 4-port Gigabit switch with 10/100Mbps support as well
- ETH0 (WAN) and ETH1 (LAN) Ports which appear as two separate Ethernet ports
- Ethernet ports indicate connection data rate
- Two optically isolated EIA-485 ports with automatic TXEN support
- One USB 2.0 high speed port (480Mbps)
- Real-Time Clock (supercap backed up)
- Software controlled Status LED
- 24VAC/DC power
- Status LEDs
- 0 - 60° C

Providing hardened circuitry and solid construction, the Automation Platform is a reliable solution for the most rugged automation systems and with its support of up to 128GB microSD cards, Flash space will never be an issue.



EIAP5G-DEV
Automation Platform

Preliminary

Overview


The Automation Platform can communicate with almost any standard network device, from Gigabit Ethernet to Wi-Fi to EnOcean to EIA-485.

The CPU has two Ethernet ports, of which one connects to the ETH1 (WAN) port. The ETH0 (LAN) ports are connected to a second port on the CPU. This allows the Automation Platform to work on two networks at the same time or to act as an IP router.

The optically isolated EIA-485 ports have automatic TXEN control so the software does not need to be concerned with controlling TXEN when transmitting messages. The USB port also supports any networking devices not already supported by the Automation Platform's wide variety of networking options or it can be used to connect to external Flash storage devices.

Unlike other off-the-shelf CPU boards, the Automation Platform supplies a software controllable Status LED which communicates to customers the status of the software.

There is also a reset IP switch which the software can read and can be used to indicate when to utilize a standard IP address and password. This is especially important so that customers can reach the device if they lose the IP address or password.



Ordering Information

<i>Model</i>	<i>Description</i>
EIAP5G-DEV	1.2GHz Automation Platform development system (contact us for information)

United States

Contemporary Control Systems, Inc.
2431 Curtiss Street
Downers Grove, IL 60515
USA

Tel: +1 630 963 7070
Fax: +1 630 963 0109

info@ccontrols.com
www.ccontrols.com

China

Contemporary Controls (Suzhou) Co. Ltd
11 Huoju Road
Science & Technology
Industrial Park
New District, Suzhou
PR China 215009

Tel: +86 512 68095866
Fax: +86 512 68093760

info@ccontrols.com.cn
www.ccontrols.asia

United Kingdom

Contemporary Controls Ltd
14 Bow Court
Fletchworth Gate
Coventry CV5 6SP
United Kingdom

Tel: +44 (0)24 7641 3786
Fax: +44 (0)24 7641 3923

ccl.info@ccontrols.com
www.ccontrols.eu

Germany

Contemporary Controls GmbH
Fuggerstraße 1 B
04158 Leipzig
Germany

Tel: +49 341 520359 0
Fax: +49 341 520359 16

ccg.info@ccontrols.com
www.ccontrols.eu